




Φ5.2x20mm IEC STANDARD FUSE RoHS Compliant & Pb-Free
HIGH BREAKING CAPACITY CERAMIC
TUBE FUSE (TIME-LAG)
高分断能力瓷保险丝管 (慢断型)

INTERRUPTING CAPACITY/分断能力:
1,500 amperes at 250V AC


Dimensions/尺寸:

Unit 单位: mm

50CT



50CT(P)



Standards/标准: IEC 60127 GB 9364

Operating Temperature/工作温度: -55°C ~125°C


Storing Temperature/储存温度: -55°C ~85°C

Resistance to soldering heat/耐焊接热性: 260°C, 10s Max

Solderability/可焊性: 245°C ±5°C, 5s ±0.5s

50CT AVERAGE I-T CHARACTERISTICS CURVE
(FOR REFERENCE ONLY)

50CT 平均 I-T 曲线图 (仅供参考)



TECHNICAL PARAMETERS/技术参数:

CATALOG NO. 目录编号	CURRENT RATING 额定电流	MAX. VOLTAGE DROP 最大电压降 (mv)	SAFETY APPROVALS 安全认证							REFERENCE (A, Sec.) (RoHS) IT 参考值
			CQC	CQC	SEMKO	VDE	BSI	UR&UR	PSE	
50CT-0200H	200mA	2100							●	0.0480
50CT-0250H	250mA	1500							●	0.0570
50CT-0315H	315mA	1100							●	0.0960
50CT-0400H	400mA	1000							●	0.1610
50CT-0500H	500mA	850							●	0.2570
50CT-0630H	630mA	650							●	0.4510
50CT-0800H	800mA	500							●	0.5532
50CT-010H	1A	350	●	●	●	●	●	●	●	1.014
50CT-013H	1.25A	300	●	●	●	●	●	●	●	2.115
50CT-016H	1.6A	200	●	●	●	●	●	●	●	4.238
50CT-020H	2A	190	●	●	●	●	●	●	●	7.120
50CT-025H	2.5A	180	●	●	●	●	●	●	●	7.781
50CT-032H	3.15A	140	●	●	●	●	●	●	●	15.46
50CT-040H	4A	100	●	●	●	●	●	●	●	37.60
50CT-050H	5A	100	●	●	●	●	●	●	●	60.95
50CT-063H	6.3A	100	●	●	●	●	●	●	●	101.3
50CT-080H	8A	100	●	●	●	●	●	●	●	188.7
50CT-100H	10A	100	●	●	●	●	●	●	●	323.4
50CT-120H	12A	80							●	539.2
50CT-125H	12.5A	80	●	●	●				●	585.1
50CT-150H	15A	80							●	934.1
50CT-160H	16A	80	●	●	●					1055

H DENOTES FOR 250V

H 表示 250V

● DENOTES FOR APPROVED

● 表示已取得安全认证

REMARK 备注:

50CT(P)-125H WITHOUT VDE/SEMKO APPROVAL

50CT(P)-125H 产品无 VDE/SEMKO 认证

50CT(P)-160H WITHOUT CQC/VDE/SEMKO APPROVAL

50CT(P)-160H 产品无 CQC/VDE/SEMKO 认证

ELECTRICAL CHARACTERISTICS/电气特性:

RATING 额定		BLOWING TIME 熔断时间			
		200mA-800mA	1A-3.15A	4A-10A	>10A
2.1In	Max. 最慢	30 minutes	30 minutes	30 minutes	30 minutes
	Min. 最快	250 ms	750ms	750 ms	1 second
2.75In	Max. 最慢	80 seconds	80 seconds	80 seconds	80 seconds
	Min. 最快	50 ms	95 ms	150 ms	150 ms
4In	Max. 最慢	5 seconds	5 seconds	5 seconds	8 seconds
	Min. 最快	5 ms	10 ms	10 ms	20 ms
10In	Max. 最慢	150 ms	150 ms	150 ms	150 ms