







# MIDDLE SERIES

## CHOGORI

### Middle Series Specifications

#### Middle Series, Rear Panel Mount & Female Pin

Description	Rear Panel Mount Screw Type, Solder	Rear Panel Mount Lock Bayonet Type, Solder	Rear Panel Mount Push Lock Type, Solder
Figure			

Drawing		<p>Note: 9.10 positions, L=17.0 other positions, L=18.0</p> 	
---------	---	--	---

Part-No.	Contacts		Part-Number		Contacts		Part-Number		Contacts		Part-Number	
		2		23002615-03		2		23002625-03		2		23002635-03
	3		23003615-03		3		23003625-03		3		23003635-03	
	4		23004615-03		4		23004625-03		4		23004635-03	
	5		23005615-03		5		23005625-03		5		23005635-03	
	6		23006615-03		6		23006625-03		6		23006635-03	
	7		23007615-03		7		23007625-03		7		23007635-03	
	8		23008615-03		8		23008625-03		8		23008635-03	
	3+5		23305615-03		3+5		23305625-03		3+5		23305635-03	
	9		23009615-03		9		23009625-03		9		23009635-03	
	10		23010615-03		10		23010625-03		10		23010635-03	
	12		23012615-03		12		23012625-03		12		23012635-03	
	14		23014615-03		14		23014625-03		14		23014635-03	
	18		23018615-03		18		23018625-03		18		23018635-03	

#### Specifications

Number of Contacts	2	3	4	5	6	7	8	3+5	9	10	12	14	18
Wire Gauge	2.5mm <sup>2</sup> (14AWG)		1.0mm <sup>2</sup> (17AWG)	0.75mm <sup>2</sup> (18AWG)		0.34mm <sup>2</sup> (22AWG)		1.0mm <sup>2</sup> +0.25mm <sup>2</sup> (17AWG +24AWG)	0.34mm <sup>2</sup> (22AWG)	0.25mm <sup>2</sup> (24AWG)			
Panel Thickness	Max. 4.0mm					Max. 4.0mm			Max. 3.0mm				
Environmental Protection	IP68					IP67			IP67				
Mechanical Life	500 mating cycles												
Operating Temperature	- 45°C - 105°C												
Voltage Rating	300V	300V	300V	125V	125V	60V	60V	125+30V	60V	30V	30V	30V	30V
Rated Current(40°C)	20A	20A	15A	10A	10A	5A	5A	15A+2A	5A	5A	2A	2A	2A