





CE



PC 4-TW



**Approval**

**Capability**

Standard	UL	IEC
Rated Voltage	300V	500V
Rated Current	30A	32A
Wire size	24-12AWG	0.2-4.0mm <sup>2</sup>
T/W/End plate	6.2/50.5/2.0mm	
Height(mm)(NS35:7.5/NS35:15/NS32)	47/54.5/52mm	
Rated surge voltage/Contamination Class	6KV/3	
Stripping length	8mm	
Screw thread/Tightening torque	M3/0.5N.m/4.5Lb-in	
Internal cylindrical gage	A4	
Insulating Material/Inflammability class	PA/V-0	

**Specification**

Specification	Model	Pieces
(1) Terminal block	PC 4-TW	50
(2) End cover	D-PC 2.5-TW	200
(3) Fixed bridge 10P	FBI 10-6	10
(4) Insertion bridge	EB 2-6 EB 3-6 EB 10-6	100 100 50
(5) Isolator bridge bar, 10P	ISSBI 10-6	10
(6) Bridge bar isolator	IS-K 4	100
(7) Separating plate	TS-K	50
(8) Test plug socket	DSB 3/10/4	100
(9) Test plug socket, insulated	DSBJ 3/13/4	100
(10) Zack Strip	ZB6	250

**HOW TO ORDER :**

-  P - 1  - 


X	X	X
Customer Request		

Series No.

No. of pole

Color

1	Gray	4	Green	7	Trans-parent
2	Blue	5	Orange	8	Yellow
3	Black	6	Red	9	White



DEGSON ELECTRONICS CO., LTD.



NAME

PC 4-TW